

 **Saeco**® SG 200 Espresso
SG 200 Instant



 **Saeco**®

Saeco. SG 200 Espresso SG 200 Instant



Small and automatic

SG 200, the completely automatic and space saving machine is available in the Instant or in the 7 or 9 g group versions - with dose adjustment ranging from 6.5 to 11 g. It also offers a full range of options as to instant product containers.

Thanks to its refined design and great autonomy, it is perfect for offices and small locations.

It can be supplied with a cabinet - available in different versions - which makes it even more pleasant and versatile as for payment systems and operating autonomy. SG 200 is easy to use and to service. It is possible to select up to 8 beverages and 4 preselections: sugar, barley/decaffeinated coffee and no cup option. The operator can modify mixer settings and product choice.

Brewing unit

The highest achievable quality of espresso is granted by Saeco automatic brewing unit, which takes and doses the coffee instantly ground and serves it to the user. Right after the erogation, the grounds are automatically discharged into the special container. Furthermore, this unit can be completely removed so that it is very easy to clean and maintain.

The group is available in 7 and 9 g versions.

Dosing grinder

The ground coffee dosing unit has a capacity ranging from 6.5 to 11 g, with manual adjustment, to better suit operators and users needs.

Plus

- Saeco brewing group: top quality, easy maintenance and cleaning
- Maximum autonomy of operation in little space
- Versatile and available in different versions
- Easy to clean and service

Safety devices

- Equipped with a software function for setting the maximum number of coffee tablets distributed. After reaching this limit, the machine stops. Only after the dump box is removed the machine is automatically reset
- Antiflooding security valve
- CE patented

Accessories

- "Base" cabinet with discharge trays. Dimensions wxhxd (mm) 410x800x537. Weight 24 kg
- Coiner and change-giving coiner device cabinet. Cabinet predisposed for change giving coiner. Dimensions wxhxd (mm) 410x800x537. Weight 24 kg
- Saeco Card kit
- Decaffeinated coffee kit
- Time Keeper kit
- Coffee grounds and liquid discharge tray kit
- Dispensing outlet safety device kit with a float
- Water softener kit (insertable in the cabinet)
- 20-litre independent tank kit (insertable in the cabinet)

Payment systems

It accepts all the most used parallel and serial payment systems with MDB, BDV and EXECUTIVE protocol in standard or master/slave set-up, as well as the Saeco Card system.

Top quality coffee




See-through coffee beans hopper



Saeco removable brewing group



User friendly



Saeco Card Kit (optional)



 **Saeco**



| Technical data | SG 200 Espresso | SG 200 Instant |
|--|--|---|
| Dimensions w x h x d (mm) | 410x672x537 | 410x672x537 |
| Height including coffee container (mm) | 757 | - |
| Weight | kg 46 | kg 44 |
| Power supply | 230V/50Hz - 120V/60Hz | 230V/50Hz - 120V/60Hz |
| Cabinet height (mm) | 800 | 800 |
| Max. total height (mm) | 1577 | 1472 |
| Water supply | water system/ independent tank | water system/ independent tank |
| Boiler | brass 350 cc | brass 350 cc |
| Power consumption | 1250W | 1380W |
| Independent tank | inside the cabinet (20 l) | inside the cabinet (20 l) |
| Number of selections | 8 | 8 |
| Number of preselections | up to 4 (+/- sugar, decaffeinated/barley, without cup) | up to 4 (+/- sugar, decaffeinated/barley, without cup) |
| Versions | 2 or 3 soluble products | 3 or 4 soluble products |
| Coffee dosing unit | ranging from 6.0 up to 11.0 g | - |
| Available cups ø (mm) | 70 standard; 73 with kit | 70 standard; 73 with kit |
| Available stirrers (mm) | 90, 105 and 115 standard | 90, 105 and 115 standard |
| Saeco Card Payment system | validator and cashless | validator and cashless |
| Product capacity | SG 200 Espresso standard 3-soluble products configuration | SG 200 Instant standard 4-soluble products configuration |
| Cups | 195 | 195 |
| Stirrer | 185 | 185 |
| Coffee beans | kg 2.0 | - |
| Soluble coffee | - | kg 0.7 |
| Milk | kg 0.85 | kg 0.85 |
| Chocolate | kg 1.7 | kg 1.7 |
| Tea | kg 2.35 | kg 2.35 |
| Sugar | kg 2.0 | kg 2.0 |
| Coffee grounds tray | 95 tablets; 350 in the cabinet | 95 tablets; 350 in the cabinet |
| Discharge fluid tank | 1500 cc; 11 l in the cabinet | 1500 cc; 11 l in the cabinet |
| Coin tray capacity | 1400 cc; 1500 cc in the cabinet | 1400 cc; 1500 cc in the cabinet |
| Product capacity modifications | 2-soluble products configuration | 3-soluble products configuration |
| Soluble coffee | - | kg 0.7 |
| Milk | kg 1.3 | kg 1.3 |
| Chocolate | kg 2.6 | kg 2.6 |

Technical specifications

- Automatic cup, sugar and stirrer dispensing
- Brewing unit available in 7 and 9 g versions
- Painted, zinc-plated sheet body
- ABS cover with transparent coffee beans tank
- Containers and tanks in transparent, food-contact approved polypropylene
- Provided with water system connection or independent water tank insertable inside the cabinet
- Pressure boiler in all versions, including the Instant model
- Air-break device with anti-overflow valve and antiflooding security solenoid valve
- Removable cup releasing device aiding checking and cleaning
- Cups and stirrers available with different standards

User interface

- 8-key keypad for direct beverage selection (receipts can be set as you like) and two keys for sugar preselection
- The operator can set two beverage keys as pre-selection for "decaffeinated/barley" and "without cup"
- 2-lines, 20-characters alphanumeric display