

Cristallo 400

Cristallo 400 is a completely automatic vending machine designed and developed to reduce maintenance and service.

Technologically advanced and extremely user-friendly, it offers up to 12 different beverages.

Main features

- Automatically dispenses cups (up to 400), sugar and stirrers
- Saeco Brewing Unit: top quality of espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB (possible Master and Slave configurations), BDV and Executive payment systems
- Standard CPU for the whole range
- Customizable settings
- High safety for customer and operator

Accessories

- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- Hot water solenoid valve kit
- 12 V DC validator kit
- Electromechanical pulse counter kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine's settings
- Eva-Dts kit



Ideas with Passion

 **Saeco**



Technical data

| | |
|---------------------------|--|
| Dimensions (w x h x d) | 577 x 1600 x 577 mm |
| Weight | 56.5 kg |
| Power supply | 230 V/50 Hz - 120 V/60 Hz |
| Power consumption | 1250 W |
| Boiler | brass |
| Water connection | 3/4" (1 - 8 bar) |
| Water supply | standard: water-supply optional: independent water tank kit |
| Coffee bean container | 1 |
| Instant product container | 4 |
| Sugar container | 1 |
| Disc mixer | 3 |
| Spiral mixer | 1 |
| Brewing unit | 7 gr - 9 gr |
| Available cups Ø | 70 - 73 mm |
| Available stirrers | 90 - 115 mm |
| Number of selections | 12 |
| Number of preselections | 4 |

Product capacity

| | |
|------------------------|----------------|
| Coffee beans | 3.0 kg |
| Instant coffee | 0.8 kg |
| Milk | 2.7 kg |
| Chocolate | 5.4 kg |
| Tea | 3.8 kg |
| Sugar | 2.6 kg |
| Cups (h 70 mm) | 400 |
| Stirrers | 400 |
| Independent water tank | 1 or 2 of 15 l |

Cristallo 400

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact-approved polypropylene
- Water, coffee and cup empty signal
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE and VDE approved

User interface

- Direct access 12-button keypad for beverage selection
- 4 preselection keys: +/-sugar, decaffeinated/barley and no-cup option
- 2-line, 20-character alphanumeric display



Always at your service:



Saeco Vending S.p.A.

Località Casone, 1066
40041 Gaggio Montano, Bologna - Italy
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com
www.saeco.com