

# Quarzo 700

Technologically advanced and easy to use and maintain, Quarzo 700 is a completely automatic vending machine that offers up to 40 different beverages.

With an extremely innovative and elegant design, it is perfectly coordinated with Smeraldo 56.

## Main features

- Automatically dispenses cups (up to 700), sugar and stirrers
- Saeco Brewing Unit (Espresso version): top quality of espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB (possible Master and Slave configurations), BDV and Executive payment systems
- Plus version equipped with 64 mm oversized grinders for an even better coffee quality
- Updated water circuit
- Standard CPU for the whole range
- Customizable settings
- High safety for customer and operator

## Accessories

- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- Preheater kit
- Hot water solenoid valve kit (two boilers version)
- Neon light kit
- 12 V DC validator kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine's settings
- Eva-Dts kit



Ideas with Passion

 **Saeco**



Technical data	Quarzo 700
Dimensions (w x h x d)	661 x 1830 x 790 mm
Weight	142 kg
Power supply	230 V/50 Hz
Power consumption	1400 W (1700 W - two boilers version)
Boiler	brass (brass and stainless steel - two boilers version)
Water connection	3/8" (0.5 - 8.0 bar)
Water supply	standard: water-supply optional: independent water tank kit
Coffee bean container	1
Instant product container	5
Sugar container	1
Disc mixer	3
Spiral mixer	1
Brewing unit	7 gr - 9 gr
Available cups Ø	70 - 73 mm
Available strainers	90 - 115 mm
Number of selections	20
Number of preselections	4

Product capacity	Quarzo 700
Coffee beans	4.2 kg
Instant coffee	0.8 kg
Milk	2.7 kg
Chocolate	5.4 kg
Tea	4.4 kg
Sugar	4.2 kg
Cups (h 70 mm)	700
Strainers	540
Independent water tank	20 l



Always at your service:

## Technical specifications

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact-approved polypropylene
- Water, coffee and cup empty signal
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture
- Neon light for the keypad
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Built-in utility outlet
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- Safety and anti-boiling thermostats for instant products (two boilers version)
- CE approved

## User interface

- Direct access 20-button keypad for beverage selection
- 4 preselection keys: +/-sugar, decaffeinated/barley and no-cup option
- 2-line, 20-character alphanumeric display



## Saeco Vending S.p.A.

Località Casona, 1066  
40041 Gaggio Montano, Bologna - Italy  
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com  
www.saecoc.com