



The C-Frame Downspray is a 360° spray jet that distributes water evenly across the wetted surface area. Stake assembly options provide savings in labor and installation time.

Features

- 45° downspray reduces the effect of wind.
- Gentle spray minimizes damage to delicate plant foliage.
- Galvanized wire stake assembly with 36" tubing.
- Three color coded frames to identify flow rates.
- "Quick" thread for easy insertion into tubing.
- Shut-Off Clip to stop flow.
- UV stabilized for long life.

Applications


Nurseries, tree lots, potted plants, home and landscaped gardens.



CFd® Downspray Black

CFd® Downspray Brown

CFd® Downspray Blue



CFd® Downspray Wire Stake Assembly

Performance		360°	
COLOR AND ORIFICE SIZE	PRESSURE (psi)	FLOW (gph)	DIAMETER (in)
Black 0.032"	10	4.8	24
	15	6.0	24
	20	7.2	20
Brown 0.035"	10	6.0	24
	15	7.5	20
	20	8.6	20
Blue 0.039"	10	7.0	24
	15	8.9	20
	20	10.5	20

CFd® Downspray

COLOR	ORIFICE SIZE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
Black	0.032"	19005	100	50	18.1
Brown	0.035"	19025	100	50	18.1
Blue	0.039"	19015	100	50	18.1

CFd® Downspray Galvanized Wire Stake Assembly with Shut-Off Clip

COLOR	TUBE LENGTH	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
Black	36"	54305	25	12	20.1
Brown	36"	54325	25	12	20.1
Blue	36"	54315	25	12	20.1

Specifications

DIMENSIONS ASSEMBLED		CFd® DOWNSPRAY	CFd® DOWNSPRAY WIRE STAKE ASSEMBLY
HEIGHT		1.3"	37.4"
WIDTH		1.0"	1.0"
DEPTH		0.3"	0.6"
WEIGHT (approx)		0.05 oz	1.00 oz
UV STABILIZED MATERIALS	FRAME STAKE ADAPTER OFF-TAKE TUBE BARB ADAPTER STAKE	acetal	acetal polypropylene PEVA acetal galvanized steel
BASE/CONNECTION TYPE: Inlet		QUICK THREAD WITH SEALING BARB 0.16"	BARB 0.16"