


Position	Qty.	Description
	1	<p><b>CHI 4-40 A-W-G-BQQV</b></p>  <p style="text-align: center;"><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: <a href="#">4J513264</a>  Horizontal, multi-stage, non-self-priming, centrifugal pump with axial suction port and radial discharge port.</p> <p>The compact unit has mechanical shaft seal according to EN 12756 and through-going motor/pump shaft.</p> <p>Pump and motor are mounted on a common baseplate and all pump components in contact with the pumped liquid are made of stainless steel.</p> <p>The motor is a 3-phase motor.</p> <p><b>Liquid:</b>  Pumped liquid: Water  Liquid temperature range: -20 .. 110 °C  Liquid temp: 20 °C  Density: 998.2 kg/m³</p> <p><b>Technical:</b>  Rated flow: 4.5 m³/h  Rated head: 30 m  Primary shaft seal: BQQV</p> <p><b>Materials:</b>  Pump housing: Stainless steel  DIN W.-Nr. 1.4401  AISI 316  Impeller: Stainless steel  DIN W.-Nr. 1.4401  AISI 316</p> <p><b>Installation:</b>  Range of ambient temperature: -15 .. 40 °C  Maximum operating pressure: 10 bar  Max pressure at stated temp: 10 bar / 110 °C  Pipe connection: Rp 1 1/4/G 1 1/4</p> <p><b>Electrical data:</b>  Power input - P1: 1010 W  Mains frequency: 50 Hz  Rated voltage: 3 x 200/346 V  Rated current: 3,9/2,3 A  Enclosure class (IEC 34-5): IP55  Insulation class (IEC 85): F</p>



Company name:

Created by:

Phone:

Date:

08/07/2016

Position	Qty.	Description						
		<p><b>Others:</b></p> <table><tr><td>Net weight:</td><td>11.9 kg</td></tr><tr><td>Gross weight:</td><td>14.3 kg</td></tr><tr><td>Shipping volume:</td><td>0.054 m<sup>3</sup></td></tr></table>	Net weight:	11.9 kg	Gross weight:	14.3 kg	Shipping volume:	0.054 m <sup>3</sup>
Net weight:	11.9 kg							
Gross weight:	14.3 kg							
Shipping volume:	0.054 m <sup>3</sup>							

Description	Value
<b>General information:</b>	
Product name:	CHI 4-40 A-W-G-BQQV
Product No:	4J513264
EAN number:	5708601033001
Price:	On request
<b>Technical:</b>	
Rated flow:	4.5 m <sup>3</sup> /h
Rated head:	30 m
Head max:	40 m
Impeller 90 mm:	4
Primary shaft seal:	BQQV
Pump version:	A
Model:	C
<b>Materials:</b>	
Pump housing:	Stainless steel DIN W.-Nr. 1.4401 AISI 316
Impeller:	Stainless steel DIN W.-Nr. 1.4401 AISI 316
Material code:	G
<b>Installation:</b>	
Range of ambient temperature:	-15 .. 40 °C
Maximum operating pressure:	10 bar
Max pressure at stated temp:	10 bar / 110 °C
Connect code:	W
Pipe connection:	Rp 1 1/4/G 1 1/4
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	-20 .. 110 °C
Liquid temp:	20 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Power input - P1:	1010 W
P2:	770 W
Mains frequency:	50 Hz
Rated voltage:	3 x 200/346 V
Rated current:	3,9/2,3 A
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
<b>Others:</b>	
Net weight:	11.9 kg
Gross weight:	14.3 kg
Shipping volume:	0.054 m <sup>3</sup>

