


Position	Qty.	Description
	1	<p>CHi 12-10 A-W-G-BQQV</p>  <p style="text-align: center;">Note! Product picture may differ from actual product</p> <p>Product No.: 4FZ20084 Horizontal, multi-stage, non-self-priming, centrifugal pump with axial suction port and radial discharge port.</p> <p>The compact unit has mechanical shaft seal according to EN 12756 and through-going motor/pump shaft.</p> <p>Pump and motor are mounted on a common baseplate and all pump components in contact with the pumped liquid are made of stainless steel.</p> <p>The motor is a 3-phase motor.</p> <p>Liquid: Pumped liquid: Water Liquid temperature range: -20 .. 110 °C Liquid temp: 20 °C Density: 998.2 kg/m³</p> <p>Technical: Rated flow: 10 m³/h Rated head: 15 m Primary shaft seal: BQQV</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4401 AISI 316 Impeller: Stainless steel DIN W.-Nr. 1.4401 AISI 316</p> <p>Installation: Range of ambient temperature: -15 .. 40 °C Maximum operating pressure: 10 bar Max pressure at stated temp: 10 bar / 110 °C Pipe connection: Rp 1 1/2/G 1 1/2</p> <p>Electrical data: Power input - P1: 1170 W Mains frequency: 50 Hz Rated voltage: 3 x 220-240D/380-415Y V Rated current: 3,6/2,1 A Starting current: 18,2/10,5 A Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F</p>



Company name:

Created by:

Phone:

Date:

08/07/2016

Position	Qty.	Description
		<p data-bbox="309 338 411 367">Others:</p> <p data-bbox="309 367 767 405">Net weight: 11.8 kg</p> <p data-bbox="309 405 767 443">Gross weight: 14.2 kg</p> <p data-bbox="309 443 783 481">Shipping volume: 0.054 m³</p>

Description	Value
General information:	
Product name:	CHi 12-10 A-W-G-BQQV
Product No:	4FZ20084
EAN number:	5700397472057
Price:	On request
Technical:	
Rated flow:	10 m ³ /h
Rated head:	15 m
Head max:	20 m
Impeller 130 mm:	1
Impeller 98 mm:	0
Primary shaft seal:	BQQV
Pump version:	A
Model:	C
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4401 AISI 316
Impeller:	Stainless steel DIN W.-Nr. 1.4401 AISI 316
Material code:	G
Installation:	
Range of ambient temperature:	-15 .. 40 °C
Maximum operating pressure:	10 bar
Max pressure at stated temp:	10 bar / 110 °C
Connect code:	W
Pipe connection:	Rp 1 1/2/G 1 1/2
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-20 .. 110 °C
Liquid temp:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	1170 W
P2:	830 W
Mains frequency:	50 Hz
Rated voltage:	3 x 220-240D/380-415Y V
Rated current:	3,6/2,1 A
Starting current:	18,2/10,5 A
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Others:	
Net weight:	11.8 kg
Gross weight:	14.2 kg
Shipping volume:	0.054 m ³
Sales region:	GB

