

Product Specifications

Hunter Pro C Controller

- ❖ 240 VAC transformer with internal junction box
- ❖ Station output 24VAC .56 Amps
- ❖ Transformer output 24VAC 1.0 Amps
- ❖ Capable of operating equivalent of 3 solenoids simultaneously
- ❖ Operating Temperature: -18 to 66° C
- ❖ NEMA rated outdoor cabinet
- ❖ CE/UL Listed
- ❖ 4 start times per program for repeat watering needs
- ❖ Up to six hours run time on each station
- ❖ Automated chronological ordering of start times/start time stacking
- ❖ 365-day calendar with leap year intelligence
- ❖ Programmable event day off allows specific day(s) to be designated as always “off”
- ❖ Rain Sensor bypass switch compatible with micro switch based sensors, displays when sensor is active
- ❖ Programmable delay between stations of zero seconds to 4 hours for well recovery or slow-closing valves
- ❖ Programmable rain delay for 1 to 7 days
- ❖ Compatible with Hunter’s SRR and ICR remote control system
- ❖ Programmable pump/master valve circuit by station
- ❖ Hunter Quick Check™ helps troubleshoot field wiring problems
- ❖ Test program feature allows for quick system checks
- ❖ Central control compatible with Hunter IMMS™ system
- ❖ Automatic module recognition; automatically identifies stations when modules are installed or removed
- ❖ Non-volatile memory backs up watering programs and current date and time
- ❖ Electronic short circuit protection; detects and skips shorted stations, no fuse to replace

