

Product Specifications

254 NAAN Sprinkler

Features:

- ❖ Solid-set or mechanically moved systems
- ❖ Heavy-duty all brass construction for durability
- ❖ Corrosion free spring and shaft made from stainless-steel
- ❖ High water distribution with spacing up to 24 m
- ❖ Plastic non-clog vane for wider range and wind-resistant droplets
- ❖ Sand and dust protection
- ❖ Body trajectory -28°

Specifications:

- ❖ Flow: 1.78 to 7.4 m³/h 7.8 to 32.7 gpm
- ❖ Pressure: 3.5 m to 6.0 bar 50 to 85 psi
- ❖ Max. spacing 24m 80 ft

Nozzle Mm	P Bar	Q m ³ /h	D m
5.0	4.0	1.900	35
	5.0	2.090	38
	6.0	2.270	40
5.5	4.0	2.270	37
	5.0	2.510	39
	6.0	2.730	40
6.0	4.0	2.670	37
	5.0	2.980	40
	6.0	3.230	42
6.3	4.0	2.890	39
	5.0	3.210	42
	6.0	3.490	45
7.0	4.0	3.530	40
	5.0	3.910	44
	6.0	4.260	48
7.5	4.0	4.070	41
	5.0	4.536	46
	6.0	4.860	50
8.5	4.0	5.210	43
	5.0	5.810	47
	6.0	6.310	51

* Standard Nozzle

