

900 Series Pop-Up


FEATURES

- Unique integrally molded "Leak-Stopper" gasket prevents any body-cap leaks
- Cap and seal utilize a "co-molded" design which provides internal support for the long term integrity of the wiper seal
- High impact virgin ABS plastic construction of body, piston and cap
- Patented Lateral discharging flush plug to aid installation
- Heavy duty stainless steel retraction spring
- Spring-loaded ratchet on all models for directional adjustment of spray pattern
- Available with female (red flush plug) or male (green flush plug) threaded pistons


OPERATING SPECIFICATIONS

- Operating pressure: 15-70 PSI, 25-70 PSI with CKV
- Recommended working pressure: 30 PSI
- Recommended working pressure with PRD: 30-70 PSI


PRD-30 Performance Graph Standard



PRD-40 Performance Graph



PRD-45 Performance Graph



DIMENSIONS

- 1/2" female pipe thread on bottom inlet



902

Body Height: 4 1/4"
Pop-Up Height: 2"
Exposed Surface Diameter: 2 1/8"



903

Body Height: 5"
Pop-Up Height: 3"
Exposed Surface Diameter: 2 1/8"



904

Body Height: 6"
Pop-Up Height: 4"
Exposed Surface Diameter: 2 1/8"



905

Body Height: 8 1/2"
Pop-Up Height: 5"
Exposed Surface Diameter: 2 1/8"



900 Series Pop-Up



906

Body Height: 9 1/2"
Pop-Up Height: 6"
Exposed Surface Diameter: 2 1/8"



912

Body Height: 15 1/2"
Pop-Up Height: 12"
Exposed Surface Diameter: 2 1/8"
• Side Inlet



906S

Body Height: 9 1/2"
Pop-Up Height: 6"
Exposed Surface Diameter: 2 1/8"
• Side Inlet

Co-molded Wiper Seal



With "Leak-Stopper" gasket eliminating body/cap leak

OPTIONS AVAILABLE

- Check Valve (-CKV): holds up to 14 feet of head
**(904, 905, 906, and 912 only)*
- In stem pressure regulating device (-PRD)
 - PRD-30 (30 PSI Outlet)
 - PRD-40 (40 PSI Outlet)
 - PRD-45 (45 PSI Outlet)**(904, 905, 906, and 912 only)*
- Reclaimed purple cap (-R)

ORDER SPECIFICATION GUIDE : Model(Option1) + Option2 + Option3 + Option4

Model	Option 1	Option 2	Option 3	Option 4
902 = 2" Pop-Up	Blank = Male Nozzle Thread on Piston F = Female Nozzle Thread on Piston	Blank = No Option -CKV = Check Valve	Blank = No Option -PRD 30/40/45 = Pressure Regulating Device	Blank = Black Cap -R = Reclaimed Purple Cap
903 = 3" Pop-Up				
904 = 4" Pop-Up				
905 = 5" Pop-Up				
906 = 6" Pop-Up				
906S = 6" Pop-Up with Side Inlet				
912 = 12" Pop-Up				

Examples

- 906 = 6" Pop-up only
- 906 - CKV - PRD45 = 6" Pop-Up with a Check Valve and 45 PSI Pressure Regulator
- 912 - PRD30 - R = 12" Pop-Up with a 30 PSI Pressure Regulator and Purple Cap

