The second secon





High performance, compact, float valve for large and medium troughs with high demand



SMOOTH-FLO DESIGN

Optimizes water flow out of the valve, **reducing turbulence**, **minimizing float bounce**, cutting water spray, and **saving your pump**.

OPTI-FLO TECHNOLOGY

Patent protected, Opti-Flo technology, optimizes water flow through the value to **help prevent blockages & improve performance in dirty water.**

SOFT-CLOSE

Patent protected, soft closing design for reliable shut-off & preventing damaging water-hammer.

FULL FLOW

Full flow design, providing flows up to 847 L/min, and preventing pump short cycling, saving your pump and energy.

HIGH VIS FLOAT

High Vis orange float for fast easy identification of water level from a distance.



Product	Body	Inlet	Thread	Lever		led Float Size	Max. Shutoff*	Max.Flow*
Number	Material	Size	Type	Length		Agricultural	(kPa)	(L/min)
93 6001 00	Acetyl	1" BSP ⁺	Tapered	n/a	-	4'' (100mm)	1,200	847

† Supplied with 3/4" and 1-1/4" Adaptors

Sales & Contact Centre

Ph: 1800 755 899 Fax: 1800 244 688 sales_orders@philmac.com.au collect_orders@philmac.com.au

Sales & Distribution Centres

NORTHERN TERRITORY 3846 Marjorie Street, Pinelands, NT 0829

SOUTH AUSTRALIA 47 Deeds Road North Plympton 5037

NEW SOUTH WALES 288 Woodpark Road Smithfield 2164

QUEENSLAND 42 Perrin Place Salisbury 4107

TASMANIA 15 Thistle Street South Launceston 7250

WESTERN AUSTRALIA 10 Sainsbury Road O'Connor, WA 6163

Head Office Philmac Pty Ltd

47-59 Deeds Road North Plympton SA 5037 Australia ABN: 17 007 873 047 www.philmac.com.au

Online Resources

www.philmac.com.au www.youtube.com/user/PhilmacAustralia



The connection you can trust.