

PRODUCT SPECIFICATION



VAN STONE FLANGES - ROTATING RING

Designed for use in cold water PVC piping systems where frequent disassembly may be required.

FEATURES

- Two piece construction
- Flange ring rotates on pipe body for easy hole alignment
- Table D and ANSI drilling
- Holes are pre drilled
- Metal backing ring not required
- Slip insertion requires heavy body PVC solvent

SPECIFICATION

- Chemical and corrosion resistant
- Material heavy bodied PVC grey
- Maximum Operating Pressure: 1033 kPa @ 25°C



VSF80

VSF100

FIXED FACE FLANGES

Designed for use in cold water PVC piping systems.

FEATURES

- One piece construction
- Table D
- Holes are pre drilled
- Metal backing ring not required
- Slip insertion requires heavy body PVC solvent

SPECIFICATION

- Chemical and corrosion resistant
- Material heavy bodied PVC grey
- Maximum Operating Pressure: 1033 kPa @ 25°C



SPF100

Models	Nominal Sizing MM	Bolt Holes	Bolt Size	Table Drilling	
VSF80	80	8	M16	D & E	ANSI
VSF100	100	8	M16	D & E	ANSI
VSF150	150	8	M16	D & E	ANSI
VSF200	200	8	M16	D & E	ANSI
VSF250	250	12	M20	D & E	ANSI
SPF50	50	4	M16	D	
SPF80	80	8	M16	D	
SPF100	100	8	M16	D	
SPF150	150	8	M20	D	

When gluing flanges we recommend using a heavy bodied PVC solvent cement, such as Christy 946BGREY or Weld On 711

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infoosa@hrproducts.com.au