



PRESSURE TANKS

DAVEY®



Supercell G Pressure Tanks

Model Numbers: 24200G

Robust hydro-pneumatic water pressure vessels of captive diaphragm design.

APPLICATIONS

Supercell G tanks can be used as storage units for water under pressure in:-

- Household, farm or industrial water pressure systems
- Hydronic heating system expansion tanks
- Water hammer arrestor systems

WHY CHOOSE THE DAVEY SUPERCCELL G TANKS?

Patented CAD2 captive diaphragm held firmly in a central position:

- Less movement allowing use of a thicker reinforced diaphragm material than a bag or bladder tank for longer life.

Diaphragm and liner design dramatically reduces the opportunity for condensation inside the air chamber.

Heavy duty butyl diaphragm meets all major worldwide requirements for potable water applications:

- Safe, non-toxic.

Safe potable grade virgin polypropylene liner seals the water from the tank shell:

- Longer tank life
- Specific wear areas reinforced for longer life of internal parts.

Deep drawn steel shell with appliance like 2 part polyurethane enamel finish and epoxy primer:

- Protected against rusting & the effects of UV light for long life.

Patented stainless steel water connection:

- Long life even in less than perfect water conditions
- Seals water and air chambers ensuring a completely leak free and maintenance free pressure vessel.

Every tank is individually tested:

- Guaranteed reliable operation.


Compliance with the strict requirements of ISO 9001, NSF Standard 61, CE/PED, WRAS and Gost quality standards:

- Consistent product quality.

DEPEND ON
DAVEY

WATER PRODUCTS

MATERIALS OF CONSTRUCTION	
Part	Material
Tank shell	Steel
Tank finish	Epoxy primed with 2 part polyurethane enamel
Diaphragm	Butyl rubber - FDA approval
Tank inner liner	Virgin copolymer polypropylene
Tank inlet	Stainless steel with patented design



OPERATING LIMITS	
Maximum operating pressure	800 kPa (116 psi)
Maximum water temperature	90°C
Minimum water temperature	1°C
Tank air pre-charge	160 kPa

HYDRAULIC PERFORMANCE – NOMINAL DRAW OFF IN LITRES													
Model	Tank Capacity (litres)	Max. Pressure Rating (kPa)	Pressure Switch Range kPa (psi)										
			150-250 (22-36)	150-300 (22-44)	200-400 (29-58)	250-400 (36-58)	250-500 (36-73)	300-600 (44-88)	500-1000 (73-145)	700-1200 (101-174)	1000-1600 (145-232)	1600-2000 (232-290)	2000-2500 (290-363)
24200G	200	1000	57.1	75.0	80.0	60.0	83.3	85.7	90.9	N/A	N/A	N/A	N/A

DIMENSIONS							
Model	Diameter	Height	Inlet (Horizontal)			Mounting Type	Shipping Weight (kg)
			Inlet centreline to bottom of tank base	Size (B.S.P Female)	Position		
24200G	534	1041	5.7	1¼"	Bottom	Free standing	38.1

All dimensions in mm unless otherwise stated.



DAVEY davey.com.au | daveynz.co.nz

This literature is not a complete guide to product usage. Further information is available from your Davey Dealer, Davey Support Centre and from the relevant product Installation and Operating Instructions. This data sheet must be read in conjunction with the relevant product Installation and Operating Instructions and all applicable statutory requirements. Product specifications may change without notice.
 © Davey is a registered trademark of Davey Water Products Pty Ltd. © Davey Water Products Pty Ltd 2013.

