



BRASS VALVES

Can be used with Diesel Applications

Temperature Range -10 to 120 Degrees C

PRESSURE RATING: 2500kPa / 355psi

| Group 33 Ball Valves – Brass FI x FI “Untested” | Imperial (Inches) | Metric (mm) | Manufacturers Code |
|---|----------------------|----------------|-----------------------|
|  | 3/8 | 10 | BVB000 |
| | 1/2 | 15 | BVB001 |
| | 3/4 | 20 | BVB002 |
| | 1 | 25 | BVB003 |
| | 1 1/4 | 32 | BVB004 |
| | 1 1/2 | 40 | BVB005 |
| | 2 | 50 | BVB006 |
| | 2 1/2 | 65 | BVB007 |
| | 3 | 80 | BVB008 |
| | 4 | 100 | BVB009 |

| Group 42 Ball Valves – Brass FI x FI Tested (DZR) -Watermark | Imperial (Inches) | Metric (mm) | Manufacturers Code |
|---|----------------------|----------------|-----------------------|
|  | 1/2 | 15 | BVBT001 |
| | 3/4 | 20 | BVBT002 |
| | 1 | 25 | BVBT003 |
| | 1 1/4 | 32 | BVBT004 |
| | 1 1/2 | 40 | BVBT005 |
| | 2 | 50 | BVBT006 |