

# **Safety Data Sheet**

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

## 1.1 Product identifier

Product name

Synonym(s)

# DRYMIX PRODUCTS

BUILDERS CHOICE DRY MIX PRODUCTS • BUILDERS CHOICE FAST SETTING CONCRETE • BUILDERS CHOICE GENERAL PURPOSE CONCRETE • BUILDERS CHOICE GREY MORTAR • CONC20 • DRY MIX PRODUCTS • FAST20 • GRM20

#### 1.2 Uses and uses advised against

Use(s) CEMENT • CONCRETE • GROUT • MASONRY CONSTRUCTION • MORTAR

# 1.3 Details of the supplier of the product

Supplier name	BGC CEMENT (DRYMIX)
Address	77 Vulcan Rd, Canningvale, WA, 6155, AUSTRALIA
Telephone	(08) 9334 4555
Fax	(08) 9334 4544
Email	cement@bgc.com.au
Website	http://www.bgc.com.au

#### 1.4 Emergency telephone number(s)

Emergency

(08) 9334 4555

# 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Skin Corrosion/Irritation: Category 2 Serious Eye Damage / Eye Irritation: Category 2A Specific Target Organ Systemic Toxicity (Single Exposure): Category 3 Carcinogenicity: Category 1A Specific Target Organ Systemic Toxicity (Repeated Exposure): Category 1

2.2 Label elements	
Signal word	DANGER
Pictogram(s)	
Hazard statement(s)	Causes skin irritation

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.



# PRODUCT NAME DRYMIX PRODUCTS

#### Prevention statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

#### Response statement(s)

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P321	Specific treatment is advised - see first aid instructions.
P362	Take off contaminated clothing and wash before re-use.
Storage statement(s)	

P403 + P233Store in a well-ventilated place. Keep container tightly closed.P405Store locked up.

#### **Disposal statement(s)**

Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

P501

Physical characteristics of cements are that they are alkaline in nature. The pH of water solution (slurry) of cements can be as high as 13.5 and may cause burns.

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
GENERAL PURPOSE CEMENT	65997-15-1	266-043-4	5 to 15%
SAND, AMORPHOUS	-	-	30 to 95%
AGGREGATE	-	-	<80%

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

Еуе	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower are recommended.

#### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

#### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.



#### 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

## 5.3 Advice for firefighters

No fire or explosion hazard exists.

## 5.4 Hazchem code

None allocated.

# 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

#### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

#### 7.3 Specific end use(s)

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
ingreatent	IVEIEIEIICE	ppm	mg/m³	ppm	mg/m³
Chromium (VI) compounds (as Cr), water soluble	SWA (AUS)		0.05		
Portland Cement	SWA (AUS)		10		
Quartz (respirable dust)	SWA (AUS)		0.1		

## **Biological limits**

No biological limit values have been entered for this product.

#### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

ChemAlert.

## PRODUCT NAME DRYMIX PRODUCTS

#### PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear an Air-line respirator or a Full-face Class P3 (Particulate) respirator.



# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

Appearance	FINE GREY POWDER, SAND AND AGGREGATE
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	> 1200°C
Evaporation rate	NOT AVAILABLE
рН	ALKALINE
Vapour density	NOT AVAILABLE
Specific gravity	3.0 to 3.2
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

# **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

## 10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

#### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

# 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

## 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

# ChemAlert.

# **11. TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
Еуе	Irritating to the eyes. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	This product contains crystalline silica and trace amounts of hexavalent chromium compounds which are classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT - single exposure	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.
STOT - repeated exposure	Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced.
Aspiration	This product is a solid and aspiration hazards are not expected to occur.

# **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No information provided.

#### 12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

## 12.4 Mobility in soil

No information provided.

## 12.5 Other adverse effects

No information provided.

# 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Waste disposal	Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).
Logialation	Dispass of in assortance with relevant level legislation

Legislation Dispose of in accordance with relevant local legislation.

# **14. TRANSPORT INFORMATION**

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

ChemAlert.

## PRODUCT NAME DRYMIX PRODUCTS

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

#### 14.5 Environmental hazards

No information provided.

#### 14.6 Special precautions for user

Hazchem code None allocated.

# **15. REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture					
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).				
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.				
	The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].				
Hazard codes	Carc. T Xi	Carcinogen Toxic Irritant			
Risk phrases	R36/37/38 R48/23 R49	Irritating to eyes, respiratory system and skin. Toxic: danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.			
Safety phrases	S22 S24/25	Do not breathe dust. Avoid contact with skin and eyes.			
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.				

# **16. OTHER INFORMATION**

Additional information CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

# ChemAlert.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists		
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds		
	CNS	Central Nervous System		
	EC No.	EC No - European Community Number		
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)		
	GHS Globally Harmonized System			
	GTEPG			
	IARC	International Agency for Research on Cancer		
	LC50	Lethal Concentration, 50% / Median Lethal Concentration		
	LD50	Lethal Dose, 50% / Median Lethal Dose		
	mg/m³	Milligrams per Cubic Metre		
	OEL	Occupational Exposure Limit		
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).		
	ppm	Parts Per Million		
	STEL Short-Term Exposure Limit			
	STOT-RE Specific target organ toxicity (repeated exposure)			
	STOT-SE	Specific target organ toxicity (single exposure)		
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons		
	SWA	Safe Work Australia		
	TLV	Threshold Limit Value		
	TWA	Time Weighted Average		
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').			
	It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.			
	While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.			
Prepared by	Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au			

[ End of SDS ]

