



Antelco® Rotor Max™ Midi Sprinklers

Applications

Greenhouses, vegetables and under tree watering.

Excellent single sprinkler distribution. Smooth rotation, robust design, durable construction. The standard sprinkler has a black colour coded 25° trajectory spinner.

Dimensions

Height: 96mm

Width: 90mm

Weight: 38grams

Features

- Easily taken apart for servicing.
- Dual outlet sealed spinner enhances performance.
- Nozzle options are coloured to identify flow.
- 1/2" MBSP inlet
- Spinner and nozzle constructed from UV stabilised acetal
- Frame constructed from polypropylene



Order Codes	Rotor Max™ Performance			Diameter (m)	Rotor Max™ Tested 0.2m Above Ground Stream (m)
	Nozzle Colour	Pressure (kPa)	Flow (Lph)		
10121055	Red 2.8mm	100	300	11.0	0.9
		200	400	13.0	1.2
		250	460	13.0	1.2
		300	500	13.0	1.4
10121005	Black 3.2mm	100	375	11.0	0.9
		200	540	13.0	1.2
		250	600	13.0	1.2
		300	660	14.0	1.3
10121065	Purple 3.8mm	100	550	11.9	0.7
		200	775	13.8	1.0
		250	875	14.0	1.1
		300	975	13.4	1.2



Antelco® Rotor Rain® Mini Sprinklers

Low trajectory with large droplets. Robust, reliable and accurate.

Features

- 3/8" MBSP inlet
- Purple nozzle – 2.8mm orifice diameter
- Break-off spray deflector for close in watering of young trees.
- Full flow spinner suspended between two bearings for reliable performance.
- Constructed from UV stabilized material; Frame – acetal, Flipper – nylon, Nozzle – acetal

Dimensions:

Height: 49mm

Width: 46mm

Weight: 8 grams



Rotor Rain® Performance Data				
Pressure (kPa)	Diameter of Throw (m)	Flow Rate (Lph)	Stream Height (m)	Deflector Diameter (m)
100	11.2	265	0.79	
150	12.8	330	0.92	4.0
200	13.0	385	1.06	
250	12.4	430	1.12	