

# Product Specifications

## Toro 570 Z Fixed Spray Sprinklers

### Features:

- ❖ Retraction flushing clears debris for reliable pop-down
- ❖ Small 2" (50 mm) diameter cap is less visible, reducing damage from exposure or vandals
- ❖ Check valve prevents low-head drainage and keeps laterals charged with water (optional)
- ❖ Stainless steel retraction spring
- ❖ Recycled water caps available
- ❖ Accepts Maxijet® nozzles for low application rate irrigation
- ❖ All bodies shipped with a flush plug in place for ease of flushing and riser pull up
- ❖ Side inlet models available on 6" (150 mm) and 12" (300 mm) sprinkler bodies for easier installation and vandal resistance
- ❖ Non-side-inlet models available on 6" (150 mm) and 12" (300 mm) sprinkler bodies
- ❖ Variable arc nozzles – SKU reduction

### Specifications:

- ❖ Radius 0-17' (0-5,1 m)
- ❖ Maximum operating pressure: 75 psi (5,2 Bar)
- ❖ Minimum operating pressure for COM models:
  - ❖ 25 psi (1,7 Bar)
  - ❖ 1/2" (13 mm) female threaded inlet
- ❖ Body diameter: 1 3/8" (35 mm) on 2P, 3P, 4P, 6P and 6P-SI models 1 5/8" (41 mm) on 12P model, 1 3/4" (44 mm) on 12P-SI models
- ❖ Cap diameter: 2" (50 mm)
- ❖ Side Inlet: 4 3/4" (120 mm) from top of sprinkler to center of side inlet
- ❖ Check valve maintains up to 10' (3 m) elevation change (optional on non-side-inlet models except 2" and 3" (50 mm and 76 mm))

