

LOW PRESSURE BLUE



Applications:

Ideal for use as a drainage hose in emergency flood disaster situations, locations with relatively small differences in elevation, for temporary water supply or drainage.

Colour: Blue

Working Temp: -0 to 60 degrees C

Features:

Lightweight, available in large diameters, this synthetic fibre and soft PVC hose is constructed in a one piece method. Resists most chemical agents.

Product Code	Diameter (mm)		Working Pressure (PSI)	Weight (Kg/m)	Roll Length (m)
	ID	OD			
LFLD025	25.0	27.5	99	0.16	100
LFLD032	32.0	34.5	99	0.20	100
LFLD040	38.0	42.7	73	0.21	100
LFLD050	51.0	54.8	65	0.29	100
LFLD063	63.0	68.4	58	0.40	100
LFLD075	76.0	80.6	58	0.57	100
LFLD100	103.0	107.0	58	0.75	100
LFLD125	127.0	131.0	44	1.01	100
LFLD150	152.0	157.2	44	1.25	100
LFLD200	204.0	211.8	44	1.93	100
LFLD250	254.0	262.4	36	2.70	100
LFLD300	305.0	314.0	30	2.90	100
LFLD350	349.0	351.8	30	3.55	100
LFLD400	405.0	412.9	30	4.20	100