

D902 Red Multi-Purpose

Non-conductive extruded rubber hose suitable for the transfer of water, air, oil and petroleum based products up to 30% aromatic content.

PRESSURE RATING

20 Bar-WP @ 3:1 SF

TEMPERATURE RATING

-20 to +70 Deg C

TUBE

Black oil resistant nitrile rubber
non-conductive

REINFORCEMENT

Plies of nylon cord

COVER

Red, oil resistant pvc/nbr rubber
non-conductive

| Part# | I.D. mm | O.D. mm | Weight kg/mt | Length metres |
|----------|------------|------------|-----------------|------------------|
| D902-006 | 6 | 13 | 0.25 | 20,213 |
| D902-008 | 8 | 15 | 0.32 | 20,213 |
| D902-010 | 10 | 17 | 0.30 | 20,213 |
| D902-012 | 12 | 21 | 0.43 | 20,213 |
| D902-016 | 16 | 26 | 0.56 | 20,213 |
| D902-019 | 19 | 29 | 0.60 | 20,213 |
| D902-025 | 25 | 36 | 0.85 | 20,213 |
| D902-032 | 32 | 45 | 1.07 | 20,152 |
| D902-038 | 38 | 52 | 1.40 | 20,122 |
| D902-051 | 51 | 76 | 1.80 | 20,61 |



MULTIPURPOSE

D902